




UC USB Phone

UTR-UC-1 (BK) Technical Specification

| ITEMS | SPECIFICATIONS |
|----------------------------------|--|
| USB interface | USB 2.0 |
| Icon printed keys | <ul style="list-style-type: none"> - Volume down + Volume up  Send  Speaker (with LED) |
| Indication LED | <ul style="list-style-type: none"> • Power LED (Red/Green): Power • MWL (Red/Green): Incoming call, VM, FWD •  (Red/Green): Mute, Speaker |
| OS Support | Windows XP (ENG, JPN) Windows Vista™ (ENG, JPN) Operability test is required for other OS languages. |
| Audio format | Sampling rate: 16 kHz 16 bit Linear PCM |
| USB Cable | Shield Type, 4.92 ft (150 cm), Type A and B Connectors |
| Power requirements | 5 V, 0.6 W (Via USB from PC) |
| Handset | Microphone sensitivity: $-45 \pm 2\text{dB(V/Pa)}$ Microphone induction frequency: 50 Hz ~ 8 kHz |
| Speaker | Sound pressure level: $88 \pm 3\text{ dB}$ Band frequency: 0 ~ 6 kHz |
| Operating temperature & humidity | Temperature: 0 ~ 40° C Humidity: 20 ~ 80% Rh |
| Dimension (w x d x h) (mm) | (All) 70 x 223.5 x 106 mm, (Cradle) 70 x 223.5 x 68 mm, (Handset) 54 x 216 x 59 mm |
| Weight (lb) | (All) 1.23 lb, (Cradle) 0.70 lb, (Handset) 0.53 lb |
| Color | Black |