

# The scalable compact rack server

## NEC Express5800/R120e-2M

POWERFUL AND ENERGY EFFICIENT SERVERS FOR THE MOST DEMANDING APPLICATIONS



**HIGH PERFORMANCE**

**SUPERIOR ENERGY EFFICIENCY**

**SIMPLIFIED MANAGEABILITY**

### Scalable and Green

The Express5800/R120e-2M combines outstanding performance, reliability, and energy savings with green technology. In addition, the platform features internal scalability and large memory capacity for future growth. The server operates in temperatures as high as 40 degrees Celsius (104 degrees Fahrenheit), which reduces the total power consumption by lowering cooling requirements.

### For Compute-intensive Environments

The Express5800/R120e-2M is an Intel® processor-based dual-socket 2U rack server designed for memory- and processor-intensive applications. The R120e-2M is perfect for virtualization solutions, database servers and consolidation of business-critical applications which all process high data volumes in the background while running primary tasks.

### High Performance

- Support for the latest Intel® Xeon® E5-2600 v2 product family 12-core processors for maximum energy efficiency and performance
- Up to 1.5 TB memory—ideal for virtualization solutions
- 10 Gb network controller and RAID controller with dual-core I/O processor for high I/O throughput

### Superior Energy Efficiency

- Industry-leading intelligent fan control to minimize cooling power with individually optimized fan speeds
- 80 PLUS® Platinum certified power supply
- Selectable power supply units (450 Watt, 800 Watt, 1000 Watt) and cold-standby mode maximize power conversion efficiency for any size system

### Simplified Manageability

- Integrated EXPRESSSCOPE Engine 3 technology provides extensive remote management capabilities enabling direct access to the controller without special software
- EXPRESSBUILDER and ESMPRO suite enable easy installation, configuration, and remote monitoring

## HARDWARE SPECIFICATION

MODEL	Express5800/R120e-2M
Form factor / height	2U Rack
Number of processors	1 to 2
Processors	Intel® Xeon® Processor E5-2609 v2 (2.50 GHz/4-core/10 MB) Intel® Xeon® Processor E5-2620 v2 (2.10 GHz/6-core/15 MB) Intel® Xeon® Processor E5-2630 v2 (2.60 GHz/6-core/15 MB) Intel® Xeon® Processor E5-2630L v2 (2.40 GHz/6-core/15 MB) Intel® Xeon® Processor E5-2637 v2 (3.50 GHz/4-core/15 MB) Intel® Xeon® Processor E5-2640 v2 (2 GHz/8-core/20 MB) Intel® Xeon® Processor E5-2650 v2 (2.60 GHz /8-core/20 MB) Intel® Xeon® Processor E5-2660 v2 (2.20 GHz /10-core/25 MB) Intel® Xeon® Processor E5-2670 v2 (2.50 GHz/10-core/25 MB) Intel® Xeon® Processor E5-2690 v2 (3 GHz/10-core/25 MB) Intel® Xeon® Processor E5-2695 v2 (2.40 GHz/12-core/30 MB) Intel® Xeon® Processor E5-2697 v2 (2.70 GHz/12-core/30 MB)
Memory type	DDR3-1600 ECC LV UDIMM, DDR3-1600 ECC LV RDIMM, DDR3-1866 ECC RDIMM, DDR3-1600 ECC LV LRDIMM
Memory slots	24
Maximum memory	1.5 TB
Storage type	Hot plug 2.5-inch SAS and SATA HDD, Hot plug 2.5-inch SAS SSD
Maximum internal drive bays	8 to 16 with optional drive cage
Maximum internal storage	19.2 TB
Removable media	1 bay for optical drive, 1 bay for internal tape drive
Expansion slots	3 PCIe x8 Gen 3, 2 PCIe x4 Gen 3, 1 PCIe x8 Gen 3 for a RAID controller, 1 PCIe x8 Gen 3 for a dedicated network controller * The slot mix changes by installing optional riser cards
Video (VRAM)	Integrated in the server management controller (32 MB)
Network	2 1000BASE-T plus 1 100BASE-TX for management
Maximum power consumption	920 VA / 910 Watt (at 100 VAC)
Redundant power supply	Optional, hot plug
Redundant cooling fan	Optional, hot plug
Power supplies	450 Watt, 800 Watt, 1000 Watt
Systems management	EXPRESSSCOPE Engine 3
Interface	2 VGA, 1 to 2 serial, 6 USB 2.0 (plus 3 internal USB 2.0), 2 LAN, 1 management LAN
Dimensions (W x D x H) and maximum weight	448.0 x 735.0* x 87.2 mm / 17.6 x 28.9* x 3.4 in / 33 kg / 72.75 lbs. * 770.0 mm / 30.3 in depth with 1000 Watt PSU
Temperature and humidity conditions (non-condensing)	Operating: 10 to 40* °C / 50 to 104* °F, 20 to 80%, Non-operating: -10 to 55 °C / 14 to 131 °F, 20 to 80% * In specific configurations, the operable ambient temperature is up to 35°C/95°F
Operating systems and virtualization software	Microsoft® Windows Server® 2008 Standard / Enterprise Microsoft® Windows Server® 2008 Standard (x64) / Enterprise (x64) Microsoft® Windows Server® 2008 R2 Standard / Enterprise Microsoft® Windows Server® 2012 Standard / Datacenter Red Hat® Enterprise Linux® 5 Red Hat® Enterprise Linux® 6 VMware® ESX™i 5

Note : For Linux support, go to the NEC website at <http://www.nec.com/global/prod/express/linux/>, or contact our sales representative

©Copyright 2013 NEC Corporation. The information and specifications contained in this publication are subject to modification without prior notice. Microsoft and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Intel, Intel Logo, Pentium, Pentium Inside, Xeon, and Xeon Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Linux is a trademark of Linus Torvalds. Red Hat is a registered trademark of Red Hat, Inc. in the U.S. VMware is a registered trademark or trademark of VMware, Inc. in the United States and/or other jurisdictions. All other names of products and brands cited are the property of their respective owners. NEC is not responsible for photographic or typing errors.



Asia (APAC)  
NEC Corporation

7-1, Shiba 5-chome Minato-ku  
Tokyo 108-8001 Japan

[www.nec.com/express](http://www.nec.com/express)

Europe (EMEA)  
NEC Enterprise Solutions

Anton Philipsweg 1  
1223 KZ Hilversum  
The Netherlands  
+31 35 6899111

[www.nec-itplatform.com](http://www.nec-itplatform.com)

North America  
NEC Corporation of America  
Information Technology Group

2880 Scott Blvd.  
Santa Clara, CA 95050 U.S.  
+1 866 632 3226

[www.necam.com/servers](http://www.necam.com/servers)