

# UNIVERGE

## SV9500SE Model

ENTERPRISE COMMUNICATIONS  
PLATFORM

**The UNIVERGE SV9500SE Model is a robust, feature-rich system that is ideal for geographically distributed businesses and enterprises. It is designed to help solve today's communications and collaboration challenges and offers easy integration with NEC's unique vertical solutions.**



### UNIVERGE SV9500SE Model AT A GLANCE

- > 1.5U 19-inch rack high-availability Appliance Server with Intel® Core CPU Options
- > Geographic redundancy for main CPU backup and remote site survivability
- > Multiline SIP Client and multiple SIP carrier support
- > Wide-range of endpoints for all IP extensions/digital/ analog
- > Seamless and flexible deployment with up to 1,536 IP extensions/trunks in one system
- > Hospitality feature options
- > Global regulatory and environmental compliances including FCC, UL/CSA, CE Marking, Industry Canada, RoHS, REACH and Section 508 Compliant



### CUSTOMIZABLE FOR SPECIFIC REQUIREMENTS

- The SV9500SE Model communications platform offers:
- > Powerful Unified Communications with Mobility and Unified Messaging integrated within the solution
  - > Various deployment options – centralized (single/branch offices) & distributed, and private or hybrid cloud
  - > Latest upgradeable communications technology – protect your investment
  - > Both SIP and ISDN technology for a future-proof solution
  - > 19-inch stackable chassis architecture which supports server functions, media gateways and media converters in a single unit

**PLATFORM**

<b>1.5U Chassis Model</b>	NEC Communications Platform with Intel Core Processor
	1.5 Rack Units high, 19 inches wide

**SYSTEM SPECIFICATIONS**

<b>Applications</b>	UC Desktop/Mobile Client/Softphone
	UC Attendant/Contact Center/Operator
	Internal/External ACD
	Voicemail/Unified Communications System
	Emergency On-site Notification
	3rd Party Hospitality Middleware Interface
<b>Stations</b>	NEC IP Terminals
	Standard SIP Terminals
	Digital Terminals
	Analog Terminals
	DECT Business Mobility Solutions
<b>Networking</b>	SIP Trunk
	PRI Trunk
	Analog Trunk
	CCIS IP Network
<b>Gateways</b>	UG50
	1U MPC
	MGSIP128 and Virtualized MG-SIP
<b>Survivability</b>	Geo-Redundancy: GR-Node and SR-Node
<b>Capacity</b>	Stations: 1,200 IP ports per system
	Trunks: 1,536 ports per system
	GR-Node: 7 Nodes/1,536 ports each
	SR-Node: 255 units per system
	SR-Node: 1,536 ports each
	CCIS: 252 nodes

**PERIPHERAL EQUIPMENT SPECIFICATIONS**

<b>UG50</b>	2 Rack Units high, 19 inches wide
	5 slots
	Digital/Analog Stations
	Analog COT
	ISDN PRI Trunk
<b>1U MPC</b>	1 Rack Units high, 19 inches wide
	2 slots
	Redundant AC power option
	32ch conference/MOH/Announcements
<b>MGSIP128</b>	1.5 Rack Units high, 19 inches wide
	128ch SIP Trunk
<b>Regulatory Compliance</b>	FCC
	UL/CSA
	Section 508 compliant
	CE Marking
	Industry Canada(IC) CS-03
	RoHS/REACH

**SV9500 COMMUNICATIONS PLATFORM COMPARISON**

Feature	SV9500SE Model	SV9500 Appliance Model	SV9300
UG50 Connection	✓	✓	-
TDM PIR Connection	-	✓	-
UMGi	-	✓	-
Geographic Redundancy (GR-Node) for Main CPU Back-up	✓	✓	-
Geographic Redundancy (SR-Node(S)) for Remote Site Survivability	✓	✓	-
T1/E1 based CCIS	-	✓	✓
CCIS over IP	✓	✓	✓
FCCS over IP	-	✓	-
Hotel/Motel	✓	✓	✓
Location Diversity	-	✓	-
Internal ACD	✓	✓	-
Max. Capacity	1,536	16,000	1,536

NEC and the NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with © or TM are registered trademarks or trademarks of their respective owners. Models may vary for each country, and due to continuous improvements this specification is subject to change without notice. Please refer to your local NEC representative(s) for further details.

**Corporate Headquarters (Japan)**  
 NEC Corporation  
[www.nec.com/univerge](http://www.nec.com/univerge)

For further information please contact NEC Corporation or: